



Secondary Suites are not permitted in this zone

****Please be advised that this handout is a Zoning Bylaw summary only. See Zoning Bylaw for complete information.****

Building Permit Number : _____

PROPERTY INFORMATION

Address : _____
 Lot Depth : _____ Min. Basement El : _____
 Lot Width : _____ Prop. Basement El : _____
 Lot Area : _____
 Lot # : _____ Plan: _____

COVENANTS REGISTERED ON TITLE:

Comprehensive Design :	Y / N	
Geotechnical :	Y / N	
Fish & Wildlife :	Y / N	
DP30 Area :	Y / N	
Water Management :	Y / N	
Flood Plain :	Y / N	
Stat. Right-of-Way :	Y / N	

SETBACKS

		Minimum	Proposed	Complies*
Principal Structure NOTE: Garage setback to be the greater of 5.5m or 0.6m behind principle building face NOTE: <u>Common wall</u> means the full length of the interior side wall shall be adjoined to the full length of the side wall of an adjacent building.	Front	4.0 metres	m	
	Front of attached garage	5.5 metres	m	
	Rear Lot with lane	14.0 metres	m	
	Rear no lane	6.0 metres	m	
	Rear (green belt dedicated park)	6.0 metres	m	
	Interior side	1.2 metres	m	
	Interior side (Common wall)	0.0 metres	m	
	Interior side	1.2 metres	m	
	Interior side (Common wall)	0.0 metres	m	
	Exterior Side Lot Line	3.0 metres	m	
Detached Garage Principal & Accessory buildings and structures must comply with visual clearance at intersections per Section 403.8 of the zoning bylaw	Rear Lot Line	1.5 metres	m	
	Interior Side Lot Line	1.2 metres	m	
	Interior Side (common wall)	0.0 metres	m	
	Exterior Side Lot Line	3.0 metres	m	
Separation between/to principal residential use		1.2 metres	m	
Accessory structures (Sheds) **must be located in the rear yard	Rear Lot Line	0.5 metres	m	
	Interior Side Lot Line	1.2 metres	m	
	Exterior Side Lot Line	3.0 metres	m	
	Separation between/to principal residential use		1.2 metres	m

Maximum Roof projection into the required interior side yard 0.60m (2' - 0")	m
Maximum Roof projection into the required interior side & rear yards for accessory buildings is 0.45m (1'-6")	m
Maximum Roof projection into front, rear or exterior side yard setbacks 1.25m (4' - 1")	m
Vehicular access for lots backing on a Municipal lane will be restricted to the lane	Y / N

Dwelling's Corner Grade Elevations			AVERAGE FINISHED GRADE (lot grading plans) please see reverse	
(in meters)	Left	Right	((Add Lowest of existing or proposed grades at all exterior corners (4 corners minimum))/ (# of corners used, 4 min) ____ = _____ m	
Front finished gr.	a)	c)		
Rear finished gr.	b)	d)		
			AVERAGE NATURAL GRADE (No lot grading plan) please see reverse	
Front Existing gr.	e)	g)	((Add Lowest of existing or proposed grades at all exterior corners (4 corners minimum))/ (# of corners used, 4 min) ____ = _____ m	
Rear Existing gr.	f)	h)		

BUILDING HEIGHT

Building Height measured to Mid Point between Main Roof Ridge and Eave of Highest Storey for roof pitch ≥ 4:12

Building Height measured to Highest point of THE Roof for Flat roofs or where the roof pitch < 4:12

BUILDING HEIGHT of:	Roof pitch	Maximum height permitted	Proposed	Complies
Principal Building		9.5 metres		m
Accessory bldgs & structures		4.5 metres		m

HIGHEST BUILDING FACE	Maximum	Proposed	Complies
complies with sloping 7 m Highest Building Face line (existing grades) applicable to 2 units or less	7.0m		m
complies with sloping 7 m Highest Building Face line (finished grades) applicable to 2 units or less	7.0m		m
40% exemption rule applied? (2 units or less only)	Y / N	40%	%


RETAINING WALLS	walls over 1.0 metre in height require P.Eng design	Proposed	Complies
RETAINING WALLS: maximum 1.20 m (4' - 0") height		m	

LOT COVERAGE	Maximum %	Proposed %	Maximum area (m ²)	Proposed area (in metric)
Exterior lot end unit (all bldgs & structures)	55%	%	m ²	m ²
Exterior lot on Street Corner (all bldgs & structures)	45%	%	m ²	m ²
Interior unit Lot (all bldgs & structures)	65%	%	m ²	m ²
Accessory bldgs & structures each Lot	3%	%	m ²	m ²

Planchecker _____ date: _____

BUILDING HEIGHT:



1. The *Building Height* shall be measured as the vertical distance from either:
 - a. the *Average Finished Grade*, or
 - b. the *Average Natural Grade* for subdivisions of less than three (3) *Lots* and for *infill Developments* which are not required by the Municipal Engineering Department to provide a *Comprehensive Lot Grading Plan*,



LOCALIZED DEPRESSION:

1. an existing localized depression in Natural Grade not exceeding 3 metres (9.8ft.) in width, or 20% of the building length that it abuts, whichever is less;
2. a localized depression below Finished Grade providing vehicle or pedestrian entrances to a building shall be subject to the following conditions:
 - a. only one vehicle entrance and one pedestrian entrance are shall be considered as Localized Depressions on a single family or two unit residential building.
 - b. on any side of the building in a single detached or two unit residential building, the Localized Depression width shall not exceed the lesser of 50% of the corresponding building width or:
 - i. 6.0m (20 ft.) width for vehicle access.
 - ii. 2.44m (8 ft.) wide 3.0 m² in area for a pedestrian access, or
 - iii. 7.3m (24 ft.) wide for a combined vehicle and pedestrian access
3. where a localized depression for a pedestrian entrance is completely covered by a deck attached to the storey immediately above it, the localized depression shall be exempt.
4. any combination of vehicle or pedestrian entrances and exist ing depressions remaining after finish grading shall not exceed 50% of the corresponding building width or length along any side of a building.

(a) Localized Depression in natural grade



HIGHEST BUILDING FACE EXEMPTIONS:

- a. a maximum 40% of the length of the building face can be exempt from this regulation. Different portions of the building face can be exempted, provided that the sum of their lengths does not exceed 40% of the total length of the building face;
- b. roof eaves, decks, decorative features, and the pitched roof portion of either gable ends or dormers are exempt;
- c. any portion of the roof *Structure* above the top plate is exempt from this calculation; and
- d. 100% of the length of the rear *Building Face* is exempt for *Lots* where the entire *Rear Lot Line* abuts land dedicated by subdivision for *Park* purposes within which a *Watercourse* exists, as identified on Schedule "C" - Natural Features of the Maple Ridge Official Community Plan Bylaw No. 7060-2014 or the Streamside Setback Assessment Map of the Maple Ridge Watercourse Protection Bylaw No. 6410-2006, provided that the rear *Building* elevation is identified as the highest *Building Face*.

Exceptions:

